



LED DOWNLIGHTS (ALGEMENE VERLICHTING) (GENERAL LIGHTING)



Verstelbaar LED inbouwarmatuur. Behuizing gemaakt uit gegoten aluminium, gepoederlakt in de kleuren wit, zwart of zilver. Verkrijgbaar in meerdere verlichtingshoeken. Voorzien van hoogglans spiegel. Het armatuur is 350° roteer- en 30° kantelbaar. Het armatuur is uitgevoerd met een hoogwaardig koellichaam om de lichtterugval tot een minimum te beperken. De voeding wordt separaat meegeleverd.

Toepassingsgebieden: Musea, beursstands, tentoonstellingen, winkels, representatieve ruimtes, etc.

Adjustable recessed LED downlight with die-cast aluminum body, powder-coated in white, silver or black. Multiple beam angle options. High purity anodized silver aluminum reflector. Excellent heat sink capability to minimize the luminous degradation, 350° rotation and 30° tilting. Remote LED driver is included.

Applications: Museums, trade-fair stands, exhibitions, sales areas and promotional areas, etc.

Lichtbron (Light Source): Max 12.8W High power LED

Verlichtingshoek (Beam angle): 25°/40°

Kleurtemperatuur (Color temperature): 2700K/3000K/4100K/5600K

Lichtstroom (Light output): 828LM/850LM/920LM/1200LM

Kleurweergave index (Color rendering index): Ra ≥ 85/82/80/65

Bedrijfstemperatuur (Operating temperature): -30°C - +80°C

Aantal branduren (Rated life hours): 35,000 - 50,000

LED voeding (inclusief) (LED driver (included)): (CE,UL)

Voedingsspanning (Input voltage): 100-240V AC 50/60Hz

LED-stroom (LED-current): 1050mA

Opgenomen vermogen (inclusief voeding) (Power consumption (driver included)): Max 16W

42101 / .. / .. / ..

Lichtkleur
Light color

- 0: 3000K
- 1: 4100K
- 2: 5600K
- 3: 2700K

Verlichtingshoek
Beam angle

- 1: 25°
- 2: 40°

Armatuur kleur
Fixture color

- 0: Wit (White)
- 1: Zwart (Black)
- 2: Zilver (Silver)

16W LED
Incl. separate LED Driver

