



LED DOWNLIGHTS (ALGEMENE VERLICHTING) (GENERAL LIGHTING)



LED inbouwarmatuur. De speciaal ontwikkelde behuizing met lage inbouwdiepte is gemaakt uit geëxtrudeerd aluminium, gepoederlakt in de kleuren wit, zilver of zwart. Voorzien van matte acrylaat lens. Het armatuur is uitgevoerd met een hoogwaardig koellichaam om de lichtterugval tot een minimum te beperken. Wordt compleet geleverd met voeding.

Toepassingsgebieden: Kantoren, winkels, representatieve ruimtes, musea, tentoonstellingen, kunstgalerieën, hotels, restaurants, toiletten, etc.

Recessed LED spotlight. Specially made housing with low mounting depth. Made of extruded aluminum, powder-coated in white, silver or black. Equipped with frosted acrylic diffuser. Excellent heat sink capability to minimize the luminous degradation. Remote LED driver is included.

Applications: Offices, sales areas, promotional areas, museums, exhibitions, art galleries, hotels, restaurants, toilets, etc.

Lichtbron (Light Source): SMD LED 3014 21.6W
 Verlichtingshoek (Beam angle): 100°
 Kleurtemperatuur (Color temperature): 3000K/4000K/6000K
 Lichtstroom (Light output): 1500LM/1580LM/1600LM
 Kleurweergave index (Color rendering index): Ra ≥ 82/70/65
 Bedrijfstemperatuur (Operating temperature): -30°C- +40°C
 Aantal branduren (Rated life hours): 35,000 - 50,000
 LED voeding (inclusief) (LED driver (included)): (CE,UL)
 Voedingsspanning (Input voltage): 100-240V AC 50/60Hz
 LED-stroom (LED-current): 700mA
 Opgenomen vermogen (inclusief voeding) (Power consumption (driver included)): Max 24W

42144/ .. / .. / ..

Lichtkleur
 Light color
 0: 3000K
 1: 4000K
 2: 6000K

Verlichtingshoek
 Beam angle
 1: 100°

Armatuur kleur
 Fixture color
 0: Wit (White)
 1: Zwart (Black)
 2: Zilver (Silver)

24W LED
 Incl. LED Driver

