



LED DOWNLIGHTS (ALGEMENE VERLICHTING) (GENERAL LIGHTING)



LED inbouwarmatuur. De speciaal ontwikkelde behuizing met lage inbouwdiepte is gemaakt uit geëxtrudeerd aluminium, gepoederlakt in de kleuren wit, zilver of zwart. Voorzien van matte acrylaat lens. Het armatuur is uitgevoerd met een hoogwaardig koellichaam om de lichtterugval tot een minimum te beperken. Wordt compleet geleverd met voeding.

Toepassingsgebieden: Hotels, musea, tentoonstellingen, winkels, representatieve ruimtes, (vitrine) kasten, toiletten, woonhuizen, etc.

Recessed LED spotlight. Specially made housing with low mounting depth. Made of extruded aluminum, powder coated in white, silver or black. Equipped with frosted acrylic diffuser. Excellent heat sink capability to minimize the luminous degradation. Remote LED driver is included.

Applications: Hotels, museums, exhibitions, sales areas and promotional areas, showcases, toilets, private homes, etc.

Lichtbron (Light Source): SMD LED 3528 5W

Verlichtingshoek (Beam angle): 110°

Kleurtemperatuur (Color temperature): 3000K/4000K/6000K

Lichtstroom (Light output): 480LM/505LM/580LM

Kleurweergave index (Color rendering index): Ra ≥ 82/70/65

Bedrijfstemperatuur (Operating temperature): -30°C- +40°C

Aantal branduren (Rated life hours): 35,000 - 50,000

LED voeding (inclusief) (LED driver (included)): (CE,UL)

Voedingsspanning (Input voltage): 100-240V AC 50/60Hz

LED-stroom (LED-current): 560mA

Opgenomen vermogen (inclusief voeding) (Power consumption (driver included)): Max 7.6W

42145/ .. / .. / ..

Lichtkleur
Light color

0: 3000K

1: 4000K

2: 6000K

Verlichtingshoek
Beam angle

0: 110°

Armatuur kleur
Fixture color

0: Wit (White)

1: Zwart (Black)

2: Zilver (Silver)

7.6W LED
Incl. LED Driver

